


B-TRAIN REAR

CCBR33-3-00



ENGINEERED TO PERFORM

max-atlas.com

B-TRAIN REAR

CCBR33-3-00

Max-Atlas strait top heavy duty rear B-Train 33' three (3) axles fixed suspension chassis is capable of carrying one 20' ISO container, applicable in Canada. It meets all D.O.T. regulations.





STANDARD POSITION

STANDARD SPECIFICATIONS


DIMENSIONS

OVERALL CHASSIS LENGTH 33' 6"
OVERALL CHASSIS WIDTH 102"
MAXIMUM REAR HEIGHT 48"

TARE WEIGHT

TARE WEIGHT (KG) +/- 2% 4,500kg
TARE WEIGHT (LB) +/- 2% 9,920lb
GVWR  90,000lb
GCVWR  Consult with your sales representative

LANDING GEAR

 Two speed AAR approved, square leg tubing with 10" x 11 1/2" low profile sand shoes. Lift capacity: 62,500lb, ultimate load capacity 200,000lb. Road side handle.

STRUCTURE

MAIN BEAMS Deep fabricated I-Beam with 80,000 psi and 130,000 psi material for top and bottom flanges and web, ready to receive a hydraulic cylinder.

CROSS MEMBER All crossmembers are formed from 7 gauge steel.

UPPER COUPLER ASSEMBLY Pickup plate is 5/16" high-tensile steel, AAR approved king pin with an 18" location, reinforced fore and aft by formed channels.

CENTER BOLSTER Fabricated boxed bolster with 100,000 psi high-tensile material with flip-up twistlocks.

REAR BOLSTER Fabricated boxed bolster with 100,000 psi high-tensile material with flip-up twistlocks.

REAR IMPACT GUARD Designed and tested to meet Federal regulations.

RUNNING GEAR

SUSPENSION Spring ride tridem fix suspension with single leaf springs.

AXLES

QUANTITY 3.
DESCRIPTION 5" round diameter, 77 1/2" track, 5/8" wall with 25,000lb capacity.

AXLE SPREAD 60".

BRAKES

DRUM & HUB 10 stud steel hub piloted hubs, outboard mounted cast steel drums.
BRAKE 16.5" x 7" non asbestos lining.
LUBRICATION Oil or synthetic grease.
BRAKE SYSTEM TYPE 2S/1M, 30/30 brake chambers, automatic slack adjusters.

WHEELS

RIMS Steel 8,25" X 22.5" hub piloted tubeless.
RIMS COLOUR White.

TIRES

TIRES SIZES 11R22.5, 16 ply (14 ply available).
TIRE INFLATION SYSTEM Optional.

ELECTRICAL

LIGHTING

WIRES Fully sealed and certified, meets all FMVSS and CMVSS regulations.

LAMPS Flange mounted, LED.

GENERAL SPECS

CONSPICUITY TAPE "Conspicuity marking per latest Federal Safety Standards".

FASTENERS All structural fasteners are Grade 5 or more and are zinc coated.

CONTAINER LOCKS Four (4) non-retractable twist locks.

DOCUMENT HOLDER Plastic with pressure fit see through cover lens.

MUD FLAPS Two (2) Max-Atlas anti-sail 24" x 30" black rubber mud flaps.

LETTERING Optional.

FINISH

METAL PREPARATION Clean, dry steel and NACE No. 3 /SSPC-SP-6 "Commercial Blast Cleaning".

PRIMER Urethane enriched with zinc. 10 year warranty.

TOP COAT Polyurethane top coat.



max-atlas.com

MAX-ATLAS EQUIPEMENT INTERNATIONAL INC.

371, chemin Grand-Bernier Nord
Saint-Jean-sur-Richelieu (Québec) CANADA
T 450 346-8848 • 1 888 966-8848 (TOLL FREE)
F 450 358-5077

ENGINEERED
TO PERFORM