

COMBOS

CCCO4510-3-00



ENGINEERED TO PERFORM

max-atlas.com

COMBOS

CCCO4510-3-00

A 10 pins three (3) axles spring ride heavy duty combo multi-user lead (LCV) container chassis, equipped with a pintle hook and carries a 20', 40' and 45' ISO container. Applicable in Canada. It meets all D.O.T. regulations.



20' POSITION



40' POSITION



45' POSITION

STANDARD SPECIFICATIONS

DIMENSIONS

OVERALL CHASSIS LENGTH 45' 6"

OVERALL CHASSIS WIDTH 102"


MAXIMUM REAR HEIGHT 48"

TARE WEIGHT


TARE WEIGHT (KG) +/- 2% 5,480kg

TARE WEIGHT (LB) +/- 2% 12,080lb

GVWR  95,000lb

GCVWR  Consult with your sales representative

LANDING GEAR

 Two speed AAR approved, square leg tubing with 10" x 11 1/2" low profile sand shoes. Lift capacity: 62,500lb, ultimate load capacity 200,000lb. Road side handle.

STRUCTURE

MAIN BEAMS Deep fabricated I-Beam with 80,000 psi and 130,000 psi material for top and bottom flanges and web.

CROSS MEMBER All crossmembers are formed from 7 gauge steel.

UPPER COUPLER ASSEMBLY Pickup plate is 5/16" hi tensile steel, AAR approved king pin with a 20" location, reinforced fore and aft by formed channels.

FRONT BOLSTER Fabricated front sill, 96" wide with a tapered rear full web at 45 degrees as a coupling guide. Fully recessed to protect gladhands and electrical plug.

CENTER BOLSTER HSS tubing 5" x 5", 96" wide.

REAR BOLSTER HSS tubing 8" x 6", 96" wide.

REAR IMPACT GUARD Designed and tested to meet Federal regulations.

RUNNING GEAR

SUSPENSION Spring ride tridem fixed suspension with single leaf springs.

AXLES

QUANTITY 3.

DESCRIPTION 5" round diameter, 77 1/2" track, 1/2" wall with 22,500lb capacity.

AXLE SPREAD 72" (60" available).

BRAKES

DRUM & HUB 10 stud steel hub piloted hubs, outboard mounted cast steel drums.

BRAKE 16.5" x 7" non asbestos lining.

LUBRIFICATION Oil or synthetic grease.

BRAKE SYSTEM TYPE 2S/1M, 30/30 brake chambers, automatic slack adjusters.

WHEELS

RIMS Steel 8.25" X 22.5" hub piloted tubeless.

RIMS COLOUR White.

TIRES

TIRES SIZES 11R22.5, 16 ply (14 ply available).

TIRE INFLATION SYSTEM Optional.

ELECTRICAL

LIGHTING

WIRES Fully sealed and certified, meets all FMVSS and CMVSS regulations.

LAMPS Flange mounted, LED.

GENERAL SPECS

CONSPICUITY TAPE "Conspicuity marking per latest Federal Safety Standards".

FASTENERS All structural fasteners are Grade 5 or more and are zinc coated.

CONTAINER LOCKS Four (4) retractable twist locks, two (2) non-retractable twist locks, two (2) flip-up non-retractable twist locks and two (2) pin locks.

PINTLE HOOK Rigid mount pintle hook designed for trailers and semitrailers in doubles and triples operations.

DOCUMENT HOLDER Plastic with pressure fit see through cover lens.

MUD FLAPS Two (2) Max-Atlas anti-sail 24" x 30" black rubber mud flaps.

LETTERING Optional.

FINISH

METAL PREPARATION Clean, dry steel and NACE No. 3 /SSPC-SP-6 "Commercial Blast Cleaning".

PRIMER Urethane enriched with zinc. 10 year warranty.

TOP COAT Polyurethane top coat.



max-atlas.com

MAX-ATLAS EQUIPEMENT INTERNATIONAL INC.

371, chemin Grand-Bernier Nord
Saint-Jean-sur-Richelieu (Québec) CANADA

T 450 346-8848 • 1 888 966-8848 (TOLL FREE)

F 450 358-5077

ENGINEERED
TO PERFORM