

STANDARD

CCT53-3S-00



ENGINEERED TO PERFORM

max-atlas.com

STANDARD

CCT53-3S-00

This 3 axles 53' heavy duty gooseneck chassis with slider suspension capable of hauling a heavy 53' ISO container, applicable in Canada and the United States. It meets all D.O.T. regulations.



STANDARD POSITION 53'



SLIDING SUSPENSION

STANDARD SPECIFICATIONS

DIMENSIONS

OVERALL CHASSIS LENGTH 53' 6"
OVERALL CHASSIS WIDTH 102"
MAXIMUM REAR HEIGHT 48"

TARE WEIGHT

TARE WEIGHT (KG) +/- 2% 5,100kg
TARE WEIGHT (LB) +/- 2% 11,240lb
GVWR 65,000lb • 85,000lb
GCVWR 80,000lb • Consult with your sales representative

LANDING GEAR

Two speed AAR approved, square leg tubing with 10" x 11 1/2" low profile sand shoes. Lift capacity: 62,500lb, ultimate load capacity 200,000lb. Road side handle.

Two speed AAR approved, square leg tubing with 10" x 10" low profile sand shoes. Lift capacity: 55,000lb, ultimate load capacity 160,000lb. Road side handle.

STRUCTURE

MAIN BEAMS The main beams are wide flange I beams, 12" deep at 19lbs/ft, hot rolled steel, grade 50.

SLIDER BEAM Slider frame is fabricated with HSS 3" x 5" rectangular tubing. To ease the movement it is fitted with stainless steel wear pads.

CROSS MEMBER All crossmembers are formed from 7 gauge steel.

UPPER COUPLER ASSEMBLY Pickup plate is 5/16" high-tensile steel, AAR approved king pin with an 36" location, reinforced fore and aft by formed channels.

FRONT BOLSTER Fabricated front sill, 96" wide with a tapered rear full web at 45 degrees as a coupling guide. Fully recessed to protect gladhands and electrical plug.

REAR BOLSTER HSS tubing 8" x 6", 96" wide.

REAR IMPACT GUARD Designed and tested to meet Federal regulations

RUNNING GEAR

SUSPENSION Spring ride tridem sliding suspension with single leaf springs.

AXLES

QUANTITY 3.
DESCRIPTION 5" round diameter, 77 1/2" track, 1/2" wall with 22,500lb capacity.

AXLE SPREAD 49"
(60" and 72" available in option).

BRAKES

DRUM & HUB 10 stud steel hub piloted hubs, outboard mounted cast steel drums.
BRAKE 16.5" x 7" non asbestos lining.
LUBRIFICATION Oil or synthetic grease.
BRAKE SYSTEM TYPE 2S/1M, 30/30 brake chambers, automatic slack adjusters.

WHEELS

RIMS Steel 8.25" X 22.5" hub piloted tubeless.
RIMS COLOUR White.

TIRES

TIRES SIZES 11R22.5, 16 ply (14 ply available).
TIRE INFLATION SYSTEM Optional.

ELECTRICAL

LIGHTING

WIRES Fully sealed and certified, meets all FMVSS and CMVSS regulations.

LAMPS Flange mounted, LED.

GENERAL SPECS

CONSPICUITY TAPE "Conspicuity marking per latest Federal Safety Standards".

FASTENERS All structural fasteners are Grade 5 or more and are zinc coated.

CONTAINER LOCKS Two (2) non-retractable twist locks and two (2) front pins.

DOCUMENT HOLDER Plastic with pressure fit see through cover lens.

MUD FLAPS Two (2) Max-Atlas anti-pail 24" x 24" black rubber mud flaps.

LETTERING Optional.

FINISH

METAL PREPARATION Clean, dry steel and NACE No. 3 /SSPC-SP-6 "Commercial Blast Cleaning".

PRIMER Urethane enriched with zinc. 10 year warranty.

TOP COAT Polyurethane top coat.

OPTIONAL Galvanized.



max-atlas.com

MAX-ATLAS EQUIPEMENT INTERNATIONAL INC.

371, chemin Grand-Bernier Nord
Saint-Jean-sur-Richelieu (Québec) CANADA
T 450 346-8848 • 1 888 966-8848 (TOLL FREE)
F 450 358-5077

ENGINEERED
TO PERFORM