



# The Leading Manufacturer of Container Chassis in North America



## 40' Gooseneck Tandem

Overall Length

**40'-8"**

Overall Width

**96"**

Axle Spread

**49"**

Tare Weight

**6,700 lbs**

GVWR

**73,900 lbs**

**Quality. Reliability. Durability.**

# 40' Gooseneck Tandem

## Key Features

- Carries one 40' ISO container, most commonly used chassis type, a great workhorse.
- Built to last – Our chassis are built to last with fully welded and sealed joints, “M” type bolt-on landing leg bracing, weatherproof wire harness, anti-theft STT lights, just to name a few.
- User-friendly design – Our chassis are designed with users in mind by providing perforated anti-slip lower bumper, left-side Gladhands, color-coded air hoses, and a low-profile license lamp.
- Proudly made in Canada with high-quality North American steel.
- Meets all DOT, C(F)MVSS, ISO, ANSI, SAE, and TTMA specifications.

## General Specifications

<b>Material</b>	All structural steel is ASTM-A572, Grade 50 or equivalent or better.
<b>Main Beam</b>	W12@19lb/ft, ASTM-A572, Grade 50 or equivalent. GN area will be fabricated in construction.
<b>Cross Members</b>	Minimum 9" deep channel types with integrated triangular ribs at both sides.
<b>Upper Coupler</b>	5/16" thick with 2" diameter water drain holes.
<b>Bolsters</b>	Fabricated bolster 8" wide x 8" deep, “U” channel type.
<b>Rear Bumper</b>	4" x 4" safety bumper tube, with non-skid top surface.
<b>Axle</b>	AXN 5" round axles 22,500lb. Beam capacity, 71.5" track, Semi-Fluid Grease lubricated, 16.5" x 7" brakes 1.5-28 spline automatic slack adjusters, 30/30 Brake boosters to be mounted 270 degrees FRONT, chambers.
<b>Suspension</b>	AXN, 49" axle spread suspension with multi leaf heavy duty springs.
<b>Landing Gear</b>	SAF Holland/JOST, 62,500 lbs, 2-speed, crank handle is located on the driver's side of the chassis.
<b>Hub/Drums/Bearings</b>	AXN Hub, AXN Drum Assembly, AXN Bearings, AXN Spindle nut package and Stemco seals.
<b>Wheels</b>	Steel wheels – 8.25 x 22.5 hub piloted, 5 Hand holes, with TR572/573 valve stem, Pre-painted in White color.
<b>Tires</b>	11R22.5, minimum 14 ply rated, Smartway verified.
<b>Brake System</b>	Sealco 110800 spring brake priority valve with 2S/1M ABS system.
<b>Electrical System</b>	12-volt LED lighting system.
<b>Mud Flaps</b>	24" wide and cut to length with Max-Atlas Logo.
<b>Twist Locks</b>	Buffers/TOCA Drop-in type twist locks.
<b>Miscellaneous</b>	Document holder installed on the roadside near the crank handle, Conspicuity tape installed per the FMVSS 108 standards.
<b>Fasteners</b>	All structural fasteners are Grade 5 or better and are Zinc coated.
<b>Painting</b>	Abrasive blast of all metal surfaces will be done to achieve clean bare steel. Surface will be coated with primer and topcoat. Coating supplier – PPG, Chassis Color – Black (RAL 9005), Twist lock top surface to be painted with Yellow enamel (RAL 1003) color.
<b>Marking</b>	Max-Atlas standard (includes Decal layout, VIN plate).
<b>Material</b>	All structural steel is ASTM-A572, Grade 50 or equivalent or better.

## Options Available

- Automatic Tire Inflation System
- Customer Decals
- Genset Ready
- PPG Paint color
- BlackBerry GPS
- Galvanized
- Hubodometer



**Max-Atlas International Inc.**

371 Chemin du Grand Bernier Nord  
Saint-Jean-sur-Richelieu, Québec, Canada, J3B 4S2

✉ sales@max-atlas.com

☎ 450 346-8848 • 1 888 966- 8848

🌐 www.max-atlas.com